

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 0 845 660 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
03.06.1998 Bulletin 1998/23

(51) Int. Cl.<sup>6</sup>: **G01D 18/00**, **G01L 27/00**

(21) Application number: **97120737.8**

(22) Date of filing: **26.11.1997**

(84) Designated Contracting States:  
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• **Roeckner, William**  
**Carpentersville, Illinois 60110 (US)**  
• **Rueger, Timothy**  
**Rolling Meadows, Illinois 60008 (US)**


(30) Priority: **27.11.1996 US 757178**

(71) Applicant: **MOTOROLA, INC.**  
**Schaumburg, IL 60196 (US)**

(74) Representative:  
**Williamson, Simeon et al**  
**Motorola European Intellectual**  
**Property Operations**  
**Midpoint**  
**Alencon Link**  
**Basingstoke, Hampshire RG21 7PL (GB)**

**(54) Device and method for calibrating a signal**

(57) An electronic device (10) includes a signal processor (14) receiving an input signal requiring calibration, a data storage device (38) providing calibration data to the signal processor (14), a calibration controller (32) allowing the calibration data to be written to the data storage device (38) across at least an output terminal (22), and such that the signal processor (14) produces a calibrated output signal via an output driver (30) to the output terminal (22).



**EP 0 845 660 A1**

## Description

### Field of the Invention

This invention is generally directed to signal calibration in electronic devices. More specifically, the present invention is directed to signal calibration in electronic devices wherein the calibration is achieved using preexisting pins of the electronic device.

### Background of the Invention

Prior art devices requiring calibration of signals such as pressure sensor products typically require calibration before final manufacturing steps have been completed. This can result in the pressure sensor products falling out of calibration due to packaging induced stress, media isolation effects, and other factors.

For example, it is well known in the art to use laser trimming of thin film resistors to achieve temperature compensation in calibration of gain and offset in pressure sensor products. This laser trimming requires the pressure sensor package to be opened and necessitates a post trim, or post calibration, module assembly and test. This type of calibration can limit the achievable performance of a pressure sensor product due to post calibration packaging shifts.

Other prior art pressure sensor products have electrically calibrated or trimmed modules. However, these prior art electrically calibrated pressure sensor products require the use of dedicated pins to perform the calibration functions. Thus, extra pins are needed to be manufactured into the final pressure sensor product. The advantage of this electrical calibration over the laser trimming of resistors is readily apparent. For example, the pressure sensor product can be completely assembled which allows the trim and final test to occur at the same time, thus streamlining the manufacturing process. In addition, costly laser trim hardware can be replaced with a much simpler and less expensive calibration system.

Thus, it would be desirable to have a pressure sensor or other electronic device product that can be electrically calibrated without the need for additional pins.

### Brief Description of the Drawings

For a more complete understanding of the present invention reference should be made to the drawings, where:

FIG. 1 is a block diagram of an electronic device in accordance with the present invention; and  
FIG. 2 is a block diagram of an alternative embodiment of an electronic device in accordance with the present invention.

## Detailed Description of a Preferred Embodiment

The present invention provides an electrical device comprising a signal processor receiving an input signal requiring calibration, a data storage device providing calibration data to the signal processor, a calibration controller allowing the calibration data to be written to and received from a data storage device across an output terminal of the electronic device, and wherein the signal processor produces a calibrated output signal to the output terminal. This invention allows electrical trimming of a completely assembled sensor (not shown) using as few as one existing terminal of the module. The output terminal can be reconfigured from an analog output to a serial digital input/output port by use of an identifiable voltage signal applied to the pre-existing output terminal and detected by a calibration mode detector.

FIG. 1 shows a block diagram of a preferred embodiment of the present invention. The electronic device 10 in this case includes a pressure sensor element 12; but, as those skilled in the art will appreciate, other elements or signals could be inputted to signal processor 14 across lines 16 and 18. The sensor element 12 is used for illustrative purposes only and should not be read to limit the scope of the present invention. All of the elements depicted in FIG. 1 including pressure sensor element 12 are preferably contained within a monolithic device and the completely assembled package includes external leads 20, 22, and 24, which are the power supply, output, and ground, respectively.

In normal use, signal processor 14 receives an input signal requiring calibration along lines 16 and 18 and then produces a calibrated signal through output driver 30 and across the output terminal 22.

During calibration, an external calibration signal is applied to output terminal 22. This signal is received by calibration controller 32, which includes calibration mode detector 34 and I/O (input/output) control 36. When calibration mode detector 34 determines that a calibration mode signal has been received, the detector 34 disables output driver 30 and enables I/O control 36.

Once I/O control 36 is enabled, calibration data is allowed to be written to the data storage device 38 across output terminal 22. As those skilled in the art will appreciate, data storage device 38 could be any form of non-volatile memory including EPROM, EEPROM, or fusible links. When the electronic device 10 has been properly calibrated, the signal processor 14 uses the calibration data stored in the data storage device 38 via bus 42 to produce a calibrated output signal via output driver 30 at output terminal 22.

As those skilled in the art will appreciate, the calibration mode signal that is detected by calibration mode detector 34 could be any of a number of possible signals. For example, the calibration mode signal could be an AC signal applied at a particular level and at a predetermined frequency. When calibration mode detector 34 detects this level and frequency, it disables output driver

30 and enables I/O control 36. When the calibration mode signal is initially applied at output terminal 22, the AC signal overdrives output driver 30 until the output driver is disabled by calibration mode detector 34.

Preferably, a serial data protocol is used to perform data reading and writing through output terminal 22. Preferably, Manchester encoding is used to provide a self-clocking bit stream. This allows the electronic device 10 to quickly lock to the asynchronous incoming calibration data.

The alternative embodiment of the present invention shown in FIG. 2 is essentially the same as that described above in FIG. 1. The only difference is that calibration controller 44 is also connected to power supply terminal 20 wherein a calibration mode detector 46 detects a calibration mode signal applied to power supply terminal 20. In this preferred embodiment, calibration mode detector 46 preferably detects the level of supply voltage and when the voltage exceeds a threshold amount for a predetermined period of time, the detector 46 then disables output driver 30 and enables I/O control 36. Additionally, overvoltage regulator 26 is used to isolate internal supply voltage 28 from external supply terminal 20, protecting internal circuitry from excessively high voltage levels. Calibration data can then be written to data storage device 38 across output terminal 22. As those skilled in the art will appreciate, data storage device 38 could be any form of non-volatile memory including EPROM, EEPROM, or fusible links.

In the application of this invention to a pressure sensor, electronic device 10 is subjected to known pressures at known temperatures during factory calibration. Measurements of the behavior of pressure sensor element 12 are taken at each pressure and temperature. This measurement data is used to determine calibration data to be stored in data storage device 38. The widely varying response of pressure sensor element 12 is thus calibrated or normalized over a given temperature range by the previously determined calibration data.

The calibration data adjusts the response of the pressure sensor element 12 via signal processor 14. One possible method of calibration is accomplished by signal processor 14 performing an evaluation of any of several known predetermined functions that represent a desired output characteristic of the electronic device 10. Using the response of pressure sensor element 12 and calibration data stored in data storage device 38, signal processor 14 produces a calibrated output signal via output driver 30 at output terminal 22.

Thus, there has been shown and described a specific embodiment of the invention. Further modifications and improvements will occur to those skilled in the art. All modifications retaining the basic underlying principles disclosed and claimed here in are within the scope of this invention.

## Claims

1. An electronic device (10) having at least an output terminal (22) comprising:

a signal processor (14) receiving an input signal requiring calibration;  
a data storage device (38) providing calibration data to the signal processor;  
a calibration controller (32) allowing the calibration data to be written to the data storage device (38) across at least the output terminal (22); and

wherein the signal processor (14) produces a calibrated output signal to the output terminal (22).

2. The device of claim 1 further including a pressure sensor element (12) providing the input signal to the signal processor (14).
3. The device of claim 1 or claim 2 wherein the calibration controller (32) further allows the calibration data to be read from the data storage device.
4. The device of claim 1, 2 or 3 wherein the calibration controller (32) further includes:

a calibration mode detector (34) attached to the output terminal (22); and an input controller (36) responsive to the calibration mode detector (34) controlling the calibration data written to the data storage device (38).

5. The device of claim 1, 2 and 3 wherein the calibration controller (32) further includes:

a calibration mode detector (46) attached to a terminal of the electronic device other than the output terminal (22); and  
an input controller (36) responsive to the calibration mode (46) detector and controlling the calibration data written to the data storage device (38) through the output terminal (22).

6. A pressure sensor device (10) having at least an output terminal (22), a power supply terminal (20), and a ground terminal, the pressure sensor device comprising:

a pressure sensor element (12) producing a pressure signal indicative of an applied pressure wherein the pressure signal requires calibration;  
a signal processor (14) coupled to the pressure sensor element (12) and receiving the pressure signal;  
a data storage device (38) coupled to the signal

processor (14) and providing calibration data to the signal processor (14);

an input and output control (36) connected between the data storage device (38) and the output terminal (22) and allowing the calibration data to be written to and read from the data storage device (38) via the output terminal (22); a calibration mode enabler (34) connected to the input and output control (36) and one of the output and power supply terminals (22, 20), wherein the calibration mode enabler (34) enables the input and output control (36); and

wherein the signal processor (14) produces a calibrated output signal to the output terminal (22).

7. The device of any preceding claim wherein the pressure sensor element (12) is piezoresistive.
8. The device of any preceding claim wherein the device is a monolithic device.
9. The device of any preceding claim wherein the data storage device (38) includes non-volatile memory.




FIG.1




FIG.2

**THIS PAGE BLANK (USPTO)**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 97 12 0737

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 4 481 804 A (EBERHARD ET AL) * column 3, line 37 - column 4, line 46; figure 2 *	1-7,9	G01D18/00 G01L27/00
X	US 5 008 843 A (POELSLE ET AL) * column 3, line 13 - column 4, line 26; figure 1 *	1-9	
A	US 5 321 638 A (WITNEY) * the whole document *	1-9	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			G01D G01L
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 February 1998	Examiner Lloyd, P
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**THIS PAGE BLANK (USPTO)**